

Suitable for DC power supplies & converters



SR-RM2U –DUAL containing 2 x SR250..
PSU / chargers

- 2U or 3U modules for 19 inch rack system
- Alarm options
- Metering options
- Parallel redundancy options
- Fully customised solutions

19" rack mounting is available as an option to house any of the SR... range of power supplies, DC/DC converters, etc.

A wide range of options are available with this configuration, such as MCB's for mains or battery, alarms (i.e. battery low, mains fail), metering, parallel redundancy etc.

DC distribution using MCBs is available using our 3U DIST-PANEL.

SPECIFICATIONS All specifications are typical at nominal input, full load and at 20°C unless otherwise stated.

POSSIBLE CONFIGURATIONS FOR 2U SUBRACK

- SR100 x 1 or 2
- SR250 x 1 or 2
- SR500 x 1
- SR750 x 1
- SR250 + up to 4 x 7 Ah batteries
- IEXT up to 4
- IEHR up to 2

The following items may be fitted into our 2U or 3U subracks

- MCBs, digital V/I meter, diodes for N+1 redundancy
- AC/DC power supplies
- DC/DC converters
- DC/AC inverters

PHYSICAL

Dimensions : (excluding front panel)	2U:	409W x 360D x 76H mm
	2US:	409W x 340D x 76H mm
	3U:	435W x 360D x 121H mm
Front Panel Dimensions:	2U:	484 x 88mm
	3U:	484 x 134mm
Weight: (base & lid)	2U/S:	3.8kg
	3U:	4.4kg
Rear panel:	Various types available depending on application	

CODES

SR-RM2U,SR-RM2US:	2U for SR... products
SR-RM2U-DUAL:	2U for 2 x SR250 (power supplies are front removable, rear panel included)
RM2U, +RM2US:	2U for non SR components
+RM3U:	3U for general use

