

SPH150 SERIES

LED Power Supplies: 150 Watts



Specifications

Input Voltage	90 ~ 305VAC
Frequency	47~63Hz
Input Current	0.96A @ 230VAC
Output V/A	See table
Output Power	150 watts
Output Ripple & Noise	12V @ 500mV, 15V @ 600mV, 24V @ 800mV, 36 & 48V @ 1000mV
Output Current Tolerance	±5%
Line Regulation	±2%
Load Tolerance	±3%
Rise Time	Typically 30ms (max 500ms 10-90% voltage)
Hold Up Time	Typically 15mS at 230V input
Power Factor	> 0.95
Efficiency	Model Dependent 87 ~ 89%
Inrush Current	Cold start 80A @ 230V
Leakage Current	0.75mA @ 230V 50Hz
Protection:	
Over Current	1.1 ~ 1.6% times rated current. (Auto Recovery)
Short Circuit	Hiccup mode with auto recovery
Overvoltage	Yes. Recycle input power after approx 30sec
Over Temperature	Recycle input power after unit has cooled off
Operating Temp.	-40°C ~ +70°C (80% load at +70°C)
Humidity	5~95% RH
Temp Coefficient	±0.05% per °C
IP Rating	IP65 (IP66 option)
Cooling	Free air convection
Connections	Input & Output flying leads Input Power Cord & Plug - Option
Safety	EN61347-1, EN61347-2-13
Isolation Voltage	Input – Output: 5.3KV DC 1min.
EMC	EN55015 Class B
Immunity	EN61000-4-2
Harmonics	EN61000-3-2
MTBF	225Khrs per MIL-HDBK-217F (25° C)
Mechanical	222 x 62 x 37mm 1kg

Features

- **Constant Voltage / Constant Current** operation
- Output Voltage adjustment
- Wide input range: 90 ~ 305VAC
- High Efficiency up to 89%
- Power Factor Correction typically 0.95
- IP65 sealed unit
- Output short circuit protection
- Over temperature protection
- Safety: EN61347-1 & -2
- EMC and Immunity compliant
- Optional mains power cord

Description

The **SPH150** series power supplies are designed specifically for use with LED applications and available with output voltage options from 12 ~ 48VDC.

These units can operate in **Constant Voltage** or **Constant current** mode and output voltage & current is fully adjustable, providing total flexibility.

Electronic protection turns off the power supplies in case of short circuit or overload, as well as open circuit or over temperature.

These units are designed to be hard wired in fixed installations, or with an optional power cord, that can be connected to the input terminals with a standard AC plug, for easy installation to any GPO socket / outlet.

Model	Output		Output Adjustment		Power W
	V	A	V	A	
SPH150-12A	12V	12.5A	10.5-13.5V	7.5 ~12.5A	150W
SPH150-15A	15V	10A	13.5 - 17V	6 ~ 10A	150W
SPH150-24A	24V	6.3A	22 - 27V	3.8 ~ 6.3A	150W
SPH150-36A	36V	4.2A	33 – 40V	2.5 ~ 4.2A	150W
SPH150-48A	48V	3.2A	43 - 53V	1.9 ~ 3.2A	150W

- For optional input mains power cord & plug, add **-AC** to model.




Fig 1: Typical Constant Voltage / Constant Current curve.