

HBC1K2 SERIES

AC/ DC Power Supply High Voltage Output: 1200 Watts



Features

- Designed for high voltage output 24 ~ 250vdc
- Rugged design for on-board train applications
- Fully isolated input – output 4300VDC
- Over voltage protection
- Overload and short circuit protection
- MTBF > 160,000hrs
- Specials input / output combinations on request.
- Suitable for battery charging applications - Option
- N+1 Redundancy –option
- Output DC Fail alarm -option
- Suitable for Battery Charging applications

General Specifications

Input Voltage	115 / 230vac (±15%) Selectable by internal link
Input Protection	Reverse polarity protection. Inrush current limiting Input Fuse
Isolation	Input - Output 4300vdc Input - Chassis 2250vdc Output - Chassis 500vdc
EMI	EN55022 class A
Switching Freq.	55KHz
Output voltage	See table
Output Power	1200 watts
Voltage adjustment	Customer specified
Redundancy Diode	Optional for N+1 Applications
Regulation	Line / Load : ±1% combined 10% to 100% load
Dynamic Response	5% voltage deviation for 10% to 50% load step with 1msec recovery
Output Ripple /Noise	Typically 1% pk-pk or 0.2% rms 20MHZ BW
Output Protection	Over voltage protection Current limiting (Constant Current) Short circuit protection Thermal protection
Efficiency	Model dependent typically 85%
Operating temp.	0° C to +50°C at 100% load Derate 2.5% per °C to 65°C
Cooling	Built-in fans
Environmental protection	Basic ruggedizing. Extended ruggedizing and conformal coating available as an option
MTBF	Typically 160, 000 hrs
Indicators	Optional LED
Connector	Input terminal block. Output terminal block or threaded studs Other options on request
Dimensions	315 x 127 x 127 mm (U5512)
Weight	5.2kg

Description

The **HBC1K2** AC/DC Power Supply is designed for high voltage applications up to 250VDC.

This rugged, industrial quality power supply uses field proven topology. It is a mature design with an excellent track record in numerous applications. It is fan cooled by two built-in fans.

An optional built-in redundancy diode allows parallel connection to achieve higher output power or N+1 redundancy, with output DC Fail alarm.

This chassis-mount design is optimized for low component count and high efficiency. The use of components with established reliability results in high MTBF.

Options

Output Voltage	Special voltage outputs
Terminals	Customer specified connectors
N+1 Redundancy	Output redundancy diode & Alarm
Ruggedizing	Extended ruggedizing and conformal coating available.
Remote Control	Remote ON / OFF

Model	Input V	Outputs V A	Power W
HBC1K2-125-FT	115/230VAC	125V 9A	1200w
HBC1K2- 250-FT	115/230VAC	250V 4.5A	1200W

- Other voltage options available from 24 ~ 250V.